



Name	2210	2220	2240	2260	2266	2276	2460	2466	2470	2476	2480
# of Axis	1	1	1	1	1	1	3	3	3	3	3
Upgraded Accelerometers		X	X			X			X	X	X
-55°C to +125°C	X	X	X	X	X	X	X	X	X	X	X
Integrated Cable	X	X		X			X		X		
Connector			X		X	X		X		X	X
Small Footprint			X	X	X	X					
Aluminum Case	X	X		X	X	X	X	X	X	X	
Hermetic Case			X								X
Calibration Certificate Included		X	X			X			X	X	X
Lowest g Model	2g	2g	2g	2g	2g	2g	2g	2g	2g	2g	2g
Highest g Model	400g	200g	200g	400g	400g	200g	400g	400g	200g	200g	200g
Mass (grams)	10	10	10	6	8	8	30	30	30	30	35



Frequency Response & Sensitivity by G-Range

Input Range	Model Suffix (e.g. 2460-010)	Frequency Response (Minimum, 3 dB)	Sensitivity, Differential	Output Noise, Differential (RMS, Typical)	Max. Mechanical Shock (0.1 ms)
g	#	Hz	mV/g	µg/(root Hz)	g (peak)
±2	-2	0 – 300	2000	10	2000
±5	-5	0 – 400	800	15	2000
±10	-10	0 – 600	400	23	5000
±25	-25	0 – 900	160	38	5000
±50	-50	0 – 1200	80	60	5000
±100	-100	0 – 1400	40	121	5000
±200	-200	0 – 1750	20	243	5000
±400	-400	0 – 2000	10	475	5000